

DATA SHEET

Accelerator

Description

Harmony Accelerator is a chlorine-free setting accelerator which allows a high degree of mechanical strength to be achieved within a short time, even in cold weather conditions. At low temperatures, the addition of Harmony Accelerator ensures the frost-resistance of freshly-poured concrete.

Characteristics

Type: brown liquid

Density: $1,4 \pm 0,1$

pH: $4,75 \pm 1$

Dosage: 1 - 2 % by weight of cement (or 0,7 up to 1,4 litre for 100 kg of cement).

Chlorine content: $< 0,1 \%$

Dry extract: $50 \pm 2 \%$

Packaging: 5 l oder 25 l.

Frost-resistant

Accelerated setting of concrete

Application

Harmony Accelerator is ready for use.

At a dose rate of 1 - 2% by weight of cement, the liquid must be introduced into the mixer on-site, observing a mixing time of one minute per m³ of concrete.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value. Before any application, it should be checked that the present data sheet has not been superseded by a subsequent version. Version of 16/10/2018. www.harmony-beton.com

HARMONY BETON

235 ZA des Frênes

13109 SIMIANE COLLONGUE

Téléphone : 33 442 20 10 09 Télécopie : 33 442 20 94 17

www.harmony-beton.com