

DATA SHEET

Vernis SL Permapro / Permapro SL Lacquer

Description

Harmony Permapro SL Lacquer is a methacrylate varnish in solvent phase, recommended for printed concretes or coloured acids.

Use only outside / exterior.

Characteristics

Type: Methacrylate varnish component in solvent phase

Colour: Transparent

Packaging: 1 l, 5 l, 20 l

Dosage: 1 l = 10 m² in a single coat, depending upon the porosity of the base surface.

Drying time: 2 - 4 hours for further processing, accessible after 6 hours.

Storage: 12 months in unopened original packaging, stored in a dry and frost-free location.

Guarantee: Manufacturer's liability

Tools & Cleaning

Paint roller, paint tray, tarpaulin, gloves.

Clean tools with acetone after use.

Preparation

The base surface must be resistant, sound, solid, clean, dry and free of humidity.

Use Harmony Neutral Agent or Harmony Degreaser for any cleaning required (to remove grease, oil etc).

Application

Application temperature: Minimum 10 °, Maximum 25 °.

Apply a thin and uniform film in cross passes in proportion of 1 l per 10 m².

After 2 - 3 hours, a second coat can be applied.

Drying time: walkable after 6 hours, open to traffic after 48 hours.



The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value. Before any application, it should be checked that the present data sheet has not been superseded by a subsequent version. Version of 16/10/2018. www.harmony-beton.com

HARMONY BETON

235 ZA des Frênes 13109 SIMIANE COLLONGUE

Téléphone : 33 442 20 10 09 Télécopie : 33 442 20 94 17

www.harmony-beton.com