

DATA SHEET

Agent démoulant coloré / demoulding coating

Description

Harmony Agent démoulant coloré is a ready to use coating and can be applied immediately. The product is water repellent and is used in the production of printed concrete to give the flooring a natural aged patina.

Characteristics

Type: coating

Colours: 11 Packaging: +/- 10 kg tub

Dosage: 1 kg/6m²

Storage: 24 months in unopened original packaging, stored in a dry and frost-free location.

Guarantee: Manufacturer's liability

Tools

brush, protective mask, gloves.

Application

Do not use in windy conditions.

Apply the product with a brush in a thin, even layer, over the concrete surface.

Be sure to wear a protective mask.

Seven days after application, the surface can be cleaned with a broom, vacuum cleaner or with water.

To emphasise the existing colour, or to add other colours we recommend to use our Harmony Relief Enhancer.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value. Before any application, it should be checked that the present data sheet has not been superseded by a subsequent version. Version of 16/10/2018. www.harmony-beton.com

HARMONY BETON

235 ZA des Frênes

13109 SIMIANE COLLONGUE

Téléphone : 33 442 20 10 09 Télécopie : 33 442 20 94 17

www.harmony-beton.com