

DATA SHEET

Agent démoulant liquide / liquid coating

Description

Harmony Agent démoulant liquide is a ready to use liquid coating and can be applied immediately.

The product is water repellent and is used in the production of printed concrete to give the flooring a uniform patina.

Characteristics

Type: liquid coating

Colours: transparent

Packaging: 1 l / 5 l

Dosage: 1 l + 10 m²

Storage: 12 months in unopened original packaging, stored in a dry and frost-free location.

Guarantee: Manufacturer's liability

Tools

Spray gun, brush, protective mask, gloves

Application

Apply product with a spray gun or a brush.

Before applying a varnish for protection, wash the concrete with Harmony Degreaser to remove all traces of the product.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value. Before any application, it should be checked that the present data sheet has not been superseded by a subsequent version. Version of 16/10/2018. www.harmony-beton.com

235 ZA des Frênes

13109 SIMIANE COLLONGUE

Téléphone : 33 442 20 10 09 Télécopie : 33 442 20 94 17

www.harmony-beton.com