

DATA SHEET

Badigeon PU / polyurethane varnish

Description

Harmony Badigeon PU is a one-component polyurethane lacquer for the protection of stone both indoors and outdoors.

The varnish is light and UV resistant.

Characteristics

Type: soluble one-component paint

Colours: transparent

Packaging: 4kg tub

Dryness: 60%

Dosage: 250 - 350 g/m²

Storage: 12 months in unopened original packaging, stored in a dry and frost-free location.

Guarantee: Manufacturer's liability

Tools & Cleaning

Rolling brush, paint cup, gloves.

Clean tools after use with acetone.

Soil quality

The surface to be treated must be clean and dry.

Application

Mix the product with a low speed mixer. Leave the mass for a few minutes to allow the bubbles to dissolve.

Use a grid, or a paint tray, to wring the roller after immersion in the paint to avoid over-application, which can cause blistering and foaming.

Apply a coat of 250 to 350 g / m².

Apply a maximum of 2 coats.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value. Before any application, it should be checked that the present data sheet has not been superseded by a subsequent version. Version of 16/10/2018. www.harmony-beton.com

HARMONY BETON

235 ZA des Frênes

13109 SIMIANE COLLONGUE

Téléphone : 33 442 20 10 09 Télécopie : 33 442 20 94 17

www.harmony-beton.com