

DATA SHEET

Décapant Vernis / Laquer Removing Agent

Description

Harmony Lacquer Removing Agent is a new-generation gelled paint and lacquer remover and contains no methylene chloride.

This product removes acrylic, aqueous, or solvent-borne polyurethane coatings, stains, patina, wax, epoxy floors, graffiti, and persistent adhesives (such as vinyl tile or carpet floor adhesive).

Thanks to the gel-like consistency, the application is also easy on vertical surfaces such as facades, or in the shower.

This Removing Agent neither blackens nor oxidizes metals.

Glass, faïence, stone and plaster remain unharmed.

Characteristics

Type: gel-like paint / lacquer remover

Packaging: 1 l, 5 l

Dosage: 1 litre = 1 - 2m²

Storage: 12 months in unopened original packaging, stored in a dry and frost-free location.

Guarantee: Manufacturer's liability

Tools & Cleaning

Brush (a fine and a coarse brush), spray gun with Viton seal, gloves, protection-goggles.

Clean tools in water after use.

Application

The substrate must be dry.

Apply the material with the spray gun or a brush.

Pay attention to the correct dosage: 1 litre for 1 to 2 m².

Allow the material to react and work in small successive sections.

Remove the softened foil with a spatula, steel wool or a wire brush, then rinse the surface with hot or cold water.

We recommend rinsing with a high-pressure cleaner (at least 120 bar).

The process can be repeated several times until the desired result is achieved.

The reaction and peeling times depend on the temperatures of the surface and the product: for example for a two-component epoxy expect a drying time of at least 45 to 120 minutes.

After complete removal of the product, as soon as the surface is dry the surface is ready for a new treatment.



The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value. Before any application, it should be checked that the present data sheet has not been superseded by a subsequent version. Version of 16/10/2018. www.harmony-beton.com

HARMONY BETON

235 ZA des Frênes 13109 SIMIANE COLLONGUE

Téléphone : 33 442 20 10 09 Télécopie : 33 442 20 94 17

www.harmony-beton.com