

Hydrofuge de Masse / water-repellent sealing compound

Description

Harmony water-repellent sealing compound is waterproof and prevents water or moisture from entering the floor.

Well suited for screeds of all kinds.

Characteristics

Type: water-repellent sealing compound

Colour: milky white

Packaging: 1 dose = 100g

Density: 1,01

pH: 7

Dosage: 1 dose for 1 bag of 35kg

Storage: 12 months in unopened original packaging, stored in a dry and frost-free location.

Guarantee: Manufacturer's liability

Compliant with standard: EN 934.2

Application

Harmony water-repellent sealing compound is supplied ready for use.

Step 1: Mix 2/3 of water with cement, sand, gravel in concrete mixer.

Step 2: Mix water-repellent sealing compound with the remaining water (1/3) and pour this mixture into the concrete mixer.

Knead for 5 minutes before applying.

Incorporation on site in a router: 1 litre per m³ of concrete for 350 kg cement dosage

(CPJ-CEM 1 / A (D) 52.5 or 52.5 R mixing time 1 to 3 min per m³).



The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value. Before any application, it should be checked that the present data sheet has not been superseded by a subsequent version. Version of 16/10/2018. www.harmony-beton.com

HARMONY BETON

235 ZA des Frênes 13109 SIMIANE COLLONGUE

Téléphone : 33 442 20 10 09 Télécopie : 33 442 20 94 17

www.harmony-beton.com