

DATA SHEET

Latex

Description

Harmony Latex is a synthetic resin, which is specially formulated to reinforce hydraulic binder-based mortar.

Characteristics

Type: synthetic resin

Colour: milky

pH: 7,5

Density: 1,0

Dry extract: 38,5%

Type of polymer: Styrol, Butadien

MFFT: 10–12 ° C

Binding Course: 0,150 - 0,250 l / m²

Screed: 0,550 l / m² / cm of thickness

Storage: 6 months in unopened original packaging, stored in a dry and frost-free location.

Guarantee: Manufacturer's liability

Application

The base surface must be clean and moist. If it is too dry, moisten the surface.

Mixture: Mix 1 volume of Harmony Latex and 2 volumes of water,

Then add 1 volume of cement and 2 volumes of sand (with a grain size of 0/5 mm) and knead.

Apply the mass with a broom.



Information sur le niveau d'émission
de substances volatiles dans l'air
intérieur, présentant un risque de
nuire aux personnes, aux végétaux et
aux animaux de la zone habitée
(norme NF C 6555-2)

The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value. Before any application, it should be checked that the present data sheet has not been superseded by a subsequent version. Version of 16/10/2018. www.harmony-beton.com

HARMONY BETON

235 ZA des Frênes 13109 SIMIANE COLLONGUE

Téléphone : 33 442 20 10 09 Télécopie : 33 442 20 94 17

www.harmony-beton.com