

Prim Granité Universel

servicetechnique@harmony-beton.com



04 42 20 10 09



DESCRIPTION

Prim Granité Universel is a universal liquid primer composed of synthetic resin, adhesion promoter and specific (granular) fillers for the adhesion of mortars.

It can be applied both indoors and outdoors.

It regulates the porosity of substrates and adheres to substrates such as concrete, tiles, stone, etc., whether porous or not.

CARACTERISTIQUES

Type : Universal primer

Couleur : Orange

Conditionnement : 5 kg, 10 kg

Consommation : 1 kg / 10 m² (depending support)

Conservation : 12 mois dans son emballage d'origine non ouvert et stocké dans un endroit sec et hors gel

Garantie : RC fabricant

DESCRIPTION

Prim Granité Universel is a universal liquid primer composed of synthetic resin, adhesion promoter and specific (granular) fillers for the adhesion of mortars.

It can be applied both indoors and outdoors.

It regulates the porosity of substrates and adheres to substrates such as concrete, tiles, stone, etc., whether porous or not.

SUBSTRATE PREPARATION

The substrate must be resistant, healthy, solid, clean, dry and free of moisture. Use Harmony Neutral Cleaner or Harmony Wax Remover-Degreaser for any necessary cleaning (grease, oil, dirt).

IMPLEMENTATION

Do not apply to concrete or mortar less than 28 days old. Do not apply to frozen or thawing substrates.

The application temperature is between 5° and 25°. Shake well before use.

Apply Prim Granité Universel in 1 pass with a roller in a regular cross pass.

Minimum drying time: 2 hours depending on the nature of the substrate and the ambient temperature.

In case of high temperature, slightly moisten the substrate.

On a surface damaged with roughness or on a very porous surface such as an anhydrite screed, consumption may be more than 100 gr per m². It is then recommended to apply 2 coats spaced 2 hours apart.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).