

## DATA SHEET

# Renforceur de relief / Relief Enhancer

### Description

Harmony Relief Enhancer is a powder that is diluted with water.  
Applied to a printed concrete it accentuates the colour of the concrete.

### Characteristics

Type: Powder

Colours: 10

Packaging: 450 gr

Dosage: Depending on the desired effect at least 450g for 60 to 75 m<sup>2</sup>.

Storage: 12 months in unopened original packaging, stored in a dry and frost-free location.

Guarantee: Manufacturer's liability

### Tools & Cleaning

Gloves, spray gun, protection goggles, broom (with soft bristles).

Clean tools in water after use.

### Preparation

The substrate must be moistened before applying the relief enhancer.

If the relief enhancer is to be used on already painted concrete, the surface must first be cleaned with a high-pressure cleaner.

Warning: If rain risk does not apply within 24 hours.

### Application

Dilute the powder with water: 150g powder / 5 liters of water.

The colour intensity depends on the amount of water: the more water, the lighter the colour will be at the end.

If powder and water are mixed well, apply the Relief Enhancer with a spray gun.

Shake the mixture well during application to avoid lumps on the bottom of the spray gun.

Caution: The mixture can not be stored for long; depending on the temperature, it can be used

for a maximum of 2 hours.

Try to apply as even a surface as possible. After the Relief Enhancer has been applied with a spray gun, the material can be evenly spread with the help of a soft broom.

Drying time: 24 hours.

If the contrast is insufficient, or you want to add a second colour, a second layer can be applied. For this the dosage changes: 30g powder in 1 litre of water = 4 to 5 m<sup>2</sup>

Dosage may vary depending on the porosity of the concrete, the desired effects and the method of application.

Drying time: 24 hours.

## Protection

We recommend Harmony Enviro varnish, or Harmony SL Permapro varnish.

If the Relief Enhancer has been applied to a previously lacquered surface, apply the varnish with a spray gun.

For more information see the data sheets for Harmony Enviro, or Harmony SL Permapro.



The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value. Before any application, it should be checked that the present data sheet has not been superseded by a subsequent version. Version of 16/10/2018. [www.harmony-beton.com](http://www.harmony-beton.com)

HARMONY BETON

235 ZA des Frênes 13109 SIMIANE COLLONGUE

Téléphone : 33 442 20 10 09 Télécopie : 33 442 20 94 17

[www.harmony-beton.com](http://www.harmony-beton.com)